


**Unless otherwise specified:**All dimensions are in millimeters&include chem.applied/plated finish.Remove Burrs & sharp edges.

**CONFIDENTIAL:** THIS DOCUMENT AND THE INFORMATION CONTAINED IN IT ARE CONFIDENTIAL, AND CANNOT BE COPIED OR DISCLOSED IN WHOLE OR IN PART WITHOUT THE EXPRESS WRITTEN CONSENT OF BRIMOTECH SOLUTIONS BY HOLLAND

Tolerance according to NEN-ISO 406  
 Roughness according to NEN 3634  
 Shape tolerance according to NEN-ISO 1101

Nominal size (mm)	dim variation (mm)
0 - 3	±0.05
3 - 6	±0.07
6 - 10	±0.10
10 - 15	±0.12
15 - 20	±0.15
20 - 30	±0.20
30 - 50	±0.25
50 - 100	±0.30
100 - 200	±0.40
200 - 500	±0.50
500 - 1000	±0.60
1000 - 2000	±0.70
2000 - 5000	±0.80
5000 - 10000	±1.00



**Brimotech solutions** Brimotech Solutions BV  
 Koperstraat 4 8211 AK Lelystad  
 T: +31 (0)320 769103 F: +31 (0)84 8317577  
 The Netherlands  
 Info@brimotech.nl  
 www.brimotech.nl

**Part number:** EF00564  
**Description:** 8mm eyelet

Add. info:	Date last saved:	12-7-2018
Material: AISI 316 stainless steel	Date created:	19-12-2012
Finish: Polished		
Configuration: Default		
Weight: 25.58	Gram	
Drawing: EF00564	<b>F1 Force:</b> N	
Project no: -		
Revision: -		