


Unless otherwise specified: All dimensions are in millimeters & include chem. applied/plated finish. Remove Burrs & sharp edges.

CONFIDENTIAL: THIS DOCUMENT AND THE INFORMATION CONTAINED IN IT ARE CONFIDENTIAL, AND CANNOT BE COPIED OR DISCLOSED IN WHOLE OR IN PART WITHOUT THE EXPRESS WRITTEN CONSENT OF BRIMOTECH SOLUTIONS BY HOLLAND

Tolerance according to NEN-ISO 406
 Roughness according to NEN 3634
 Shape tolerance according to NEN-ISO 1101

Nominal size (mm)	dim variation (mm)
0 - 3	±0.05
3 - 6	±0.06
6 - 10	±0.08
10 - 18	±0.10
18 - 30	±0.12
30 - 50	±0.15
50 - 100	±0.20
100 - 150	±0.25
150 - 200	±0.30



General tolerance on gas springs and dampers is 2mm

Brimotech
 solutions

Brimotech Solutions BV
 Koperstraat 4 8211 AK Lelystad
 T: +31 (0)320 769103 F: +31 (0)84 8317577
 The Netherlands

Info@brimotech.nl
 www.brimotech.nl

Part number: **10420030**

Description: Gas spring stroke 500mm

Add. info: -
 Material: Steel
 Finish: RAL9005
 Configuration: **Open force [100N - 1300N]**
 Weight: 736.82 Gram
 Drawing: 10420030 **F1 Force:N**
 Project no:
 Revision:

Date last saved: 11-6-2018

Date created: 9-5-2012

DXF/STEP available on request

Scale: 1:5

Size
A4

Drawn by:
 M. Brokkaar